

Number 3
(VP325436-210)

Products Specification:

Cable Safety Padlock LG80

Part No.: LG80

Adjustable cable lockout padlocks

Cable accessories can be equipped with 3mm*0.8m or 4mm*0.8m stainless steel cable, with PVC anti-ultraviolet coating, corrosion resistance, acid and alkali resistance, and the cable length can be customized.

Adjustable cable lockout padlock

Adjustable Cable Lockout Padlock is a universal energy isolation solution ideal for unusual equipment that cannot be locked with traditional equipment.

Integrated creative design of the cable and the padlock allows you to buy no additional padlocks, which is cost-effective and more convenient to operate.

Padlock cylinder is made of copper, Copper cylinder is 6 pins, it can realize that more than 60,000pcs padlocks do not open each other.

Safety Padlock has key retaining feature, and key cannot be pulled out in open state, in order to prevent the key from being lost.

The non-conductive, non-sparking shell, Resistance of chemical, extreme temperatures and Anti-UV of the padlock can protect workers from electric shock.

Comply with OSHA standard: 1 employee = 1 padlock = 1 key.

Padlock has a label with text: "Danger locked out"/"Do not remove, property".

The lock body and key can print same code, which is convenient for management.

Can be engraved with customers' logo if required.

Suitable for use in potential explosive atmospheres EX ZONE 2



Locking: Adjust the locking position by passing the cable through the upper locking hole to complete the locking. Use cable ties to attach warning tag



Unlocking: Rotate the key to the unlocking state, push the operation key up, and the



1. Cable can be stretched at will.

2. Push the operation key to the top

3. The lock opens and the cable can be adjusted at will

