



NOTES	PASTABOS	REFERENCE DRAWINGS		REVISIONS							MAŽEIKIŲ NAFTA		MAŽEIKIAI, LITHUANIA	
1. ALL SCREWED AND SOCKET WELD VALVES WILL BE 800# RATING UNLESS OTHERWISE NOTED. 2. ALL INSTRUMENT TAG AND LINE NUMBERS HAVE THE PREFIX 31010 UNLESS OTHERWISE NOTED. 3. LOW RANGE GAUGE USED FOR REACTOR BLANKETING DURING LOADING ONLY (DISCONNECT AND BLANKOFF WHEN NOT IN USE) 4. PI VISIBLE FROM GLOBE BYPASS VALVE. 5. MANUAL LEVEL ADJUSTMENT. 6. SEE UOP SPEC 901467-633-0 SKETCH "C". PARALLEL PROBE INSTALLATION BUT ONE READOUT SIGNAL FROM ON-LINE PROBE.		TITLE	DWG NO.	NO.	DATE	BY	CHK	DESCRIPTION	 MUSTANG ENGINEERS & CONSTRUCTORS, INC. HOUSTON, TEXAS		Izomerizato gamyba  PENEX  PIPING AND INSTRUMENTATION DIAGRAM  PENEX REACTORS			
									PROJ.					
									SCALE					
									DGN BY:					
									DWG BY:					
									CHK BY:					
									APPR BY:					
									DATE:					
										FILENAME: 31010019	DWG NO: 10-310-10-D-019	REV:		