


Data Sheet

OPGW-DAB 72E9 (AA/ACS 29/29)



a General Cable company

Cross Section



**DOKUMENTACJA
POWYKONAWCZA**

Data 28. 05. 2015

Podpis Krzysztof Zieliński
upr. WKP/00103/OWOE/05

Cable Design

Central-Element: 7,4 mm filled Aluminum Tube

1st Layer: 6 x 2,5 mm Aluminum Alloy Wire + 6 x 2,5 mm Aluminum Clad Steel Wire (Right Hand Lay)

Technical Characteristics

Cable Breaking Load (CBL)	50	kN
Diameter (approx.)	12,4	mm
Weight of Cable (approx.)	365	kg/km
Modulus of Elasticity	110	kN/mm ²
Cross Section AA Wire / Cross Section ACS Wire	29 / 29	mm ²
Total Metallic Cross Section	84	mm ²
I ² t (T initial = 20°C) calculated with 8,4 kA / 1 sec	70	kA ² s
DC Resistance (T = 20°C)	0,49	Ohm/km
Coefficient of Linear Expansion	15,6	10 ⁻⁶ /K
Bending Radius; During Installation / After Installation	> 250 / > 190	mm
Standard Delivery Length / Extended Delivery Length	3 - 7 / on request	km
Temperature Range for Installation	-10 to +50	°C
Temperature Range for Transportation and Operation	-50 to +80	°C
Max. Attenuation SMF E9 at 1310 nm / at 1550 nm	0,35 / 0,21	dB/km
Max. Dispersion SMF E9; 1288 nm to 1339 nm / at 1550 nm	3,5 / 18	ps/(nm·km)
Fiber Standard: SMF E9 fibers according to ITU-T G.652.D		

All rights reserved, including, but not limited to, all rights in connection with patents or the registration of utility models or designs. Copying this document, giving it to third parties and using its contents or communicating them to third parties are expressly forbidden. Offenders shall be liable to damages. All dimensions and other values listed in this document sheet are nominal values. NSW reserves the right to make modifications to the product, its properties or its specifications at any time without notice.

Norddeutsche Seekabelwerke GmbH	Reference No.: 8525_AA_ACS_29_29_72SM	Issued 7-Oct-14
Department : TEC / PDE Signed : Oe T1,3A	Revision: 0	Page: 1(2)

Armoring: Single Layer Armoring

A single layer of armoring wires is stranded around an aluminum central buffer tube.

The specific wire materials are given in the enclosed cross section drawing.

This design provides excellent lightning protection under mechanical load and prevents the fiber from thermal stress under fault current conditions.

Before stranding the wires are pre-formed. This allows the wires to remain in position,

even when the cable is cut. Thus simple cable termination and field operations are ensured.

The standard lay direction of the outer armoring is right-hand lay, left-hand lay is available on request.

Optical Unit: Aluminum Central Buffer Tube

A hermetically sealed optical unit is formed by a central aluminum buffer tube.

Fibers are enclosed in the tube with a defined excess length in order to ensure a suitable operating window.

This means, even if a tensile load is applied to the cable causing cable elongation, there will be no fiber strain and no increase in fiber attenuation.

Central Buffer Technology provides excellent thermal and mechanical protection of the fibers.

The tube is filled with a water blocking filling compound in order to avoid water penetration and migration.

As a result, the optical fibers will not be affected by external influences.

Fiber Identification: Groups of Bundled Fibers

The fibers are colored with UV-cured ink. 10 different colors according to TIA/EIA-598 ("Telcordia Code")

are available. Customized coloring is available on request. The central buffer tube contains 72 fibers.

To allow identification, the fibers are divided in 6 groups of 12 fibers.

These groups are held together by colored binders. The following color code is used:

Fiber Color Coding:

1	2	3	4	5	6	7	8	9	10	11	12
blue,	orange,	green,	brown,	slate,	white,	red,	black,	yellow,	violet,	rose,	aqua
blue,	orange,	green,	brown,	slate,	white,	red,	black,	yellow,	violet,	rose,	aqua
blue,	orange,	green,	brown,	slate,	white,	red,	black,	yellow,	violet,	rose,	aqua
blue,	orange,	green,	brown,	slate,	white,	red,	black,	yellow,	violet,	rose,	aqua
blue,	orange,	green,	brown,	slate,	white,	red,	black,	yellow,	violet,	rose,	aqua
blue,	orange,	green,	brown,	slate,	white,	red,	black,	yellow,	violet,	rose,	aqua

Group / Binder

1 / blue
2 / orange
3 / green
4 / brown
5 / slate
6 / white

General: Applicable Standards for Cable and Wire

- IEEE Std 1138-2009: IEEE Standard Construction of Composite Fiber Optic Overhead Groundwire (OPGW) for use on Electric Utility Power Lines
- IEC 60794-4-1 Optical Fibre Cables – Part 4-1: Aerial Optical Cables for High-Voltage Power Lines
- European Standard (EN) 50182: Conductors for overhead lines, Round wire concentric lay stranded conductors
- IEC 60104 Aluminium-Magnesium-Silicon Alloy Wire for Overhead Line Conductors
- IEC 61232 Aluminium-Clad Steel Wires for Electrical Purposes
- Fiber Standard: SMF E9 fibers according to ITU-T G.652.D

**DOKUMENTACJA
POWYKONAWCZA**
28. 05. 2015
Data
KIEROWNIK BUDOWY
Podpis Krzysztof Zieliński
upr. WKP/00103/OWOE/05


Data Sheet



a General Cable company

OPGW-DAB 72E9 (AA/ACS 72/36)

Cross Section



**DOKUMENTACJA
POWYKONAWCZA**

Data 2.8.05. 2015

Podpis

KIEROWNIK BUDOWY

Krzysztof Zieliński
upr. WKP/00103/OWOE/05

Cable Design

Central-Element: 7,7 mm filled Aluminum Tube

1st Layer: 6 x 3,9 mm Aluminum Alloy Wire + 3 x 3,9 mm Aluminum Clad Steel Wire (Right Hand Lay)

Technical Characteristics

Cable Breaking Load (CBL)	67	kN
Diameter (approx.)	15,5	mm
Weight of Cable (approx.)	530	kg/km
Modulus of Elasticity	92	kN/mm ²
Cross Section AA Wire / Cross Section ACS Wire	72 / 36	mm ²
Total Metallic Cross Section	134	mm ²
I ² t (T initial = 20°C) calculated with 13,5 kA / 1 sec	181	kA ² s
DC Resistance (T = 20°C)	0,29	Ohm/km
Coefficient of Linear Expansion	17,1	10 ⁻⁶ /K
Bending Radius; During Installation / After Installation	> 310 / > 235	mm
Standard Delivery Length	3 - 5	km
Temperature Range for Installation	-10 to +50	°C
Temperature Range for Transportation and Operation	-50 to +80	°C
Max. Attenuation SMF E9 at 1310 nm / at 1550 nm	0,35 / 0,21	dB/km
Max. Dispersion SMF E9; 1288 nm to 1339 nm / at 1550 nm	3,5 / 18	ps/(nm·km)
Fiber Standard: SMF E9 fibers according to ITU-T G.652.D		

All rights reserved, including, but not limited to, all rights in connection with patents or the registration of utility models or designs. Copying this document, giving it to third parties and using its contents or communicating them to third parties are expressly forbidden. Offenders shall be liable to damages. All dimensions and other values listed in this document sheet are nominal values. NSW reserves the right to make modifications to the product, its properties or its specifications at any time without notice.

Norddeutsche Seekabelwerke GmbH	Reference No.: 8525_AA_ACS_72_36_72SM	Issued 7-Oct-14
Department : TEC / PDE Signed : Oe T1,3A	Revision: 0	Page: 1(2)

Armoring: Single Layer Armoring

A single layer of armoring wires is stranded around an aluminum central buffer tube.

The specific wire materials are given in the enclosed cross section drawing.

This design provides excellent lightning protection under mechanical load and prevents the fiber from thermal stress under fault current conditions.

Before stranding the wires are pre-formed. This allows the wires to remain in position, even when the cable is cut. Thus simple cable termination and field operations are ensured.

The standard lay direction of the outer armoring is right-hand lay, left-hand lay is available on request.

Optical Unit: Aluminum Central Buffer Tube

A hermetically sealed optical unit is formed by a central aluminum buffer tube.

Fibers are enclosed in the tube with a defined excess length in order to ensure a suitable operating window.

This means, even if a tensile load is applied to the cable causing cable elongation, there will be no fiber strain and no increase in fiber attenuation.

Central Buffer Technology provides excellent thermal and mechanical protection of the fibers.

The tube is filled with a water blocking filling compound in order to avoid water penetration and migration.

As a result, the optical fibers will not be affected by external influences.

Fiber Identification: Groups of Bundled Fibers

The fibers are colored with UV-cured ink. 10 different colors according to TIA/EIA-598 ("Telcordia Code") are available. Customized coloring is available on request. The central buffer tube contains 72 fibers.

To allow identification, the fibers are divided in 6 groups of 12 fibers.

These groups are held together by colored binders. The following color code is used:

Fiber Color Coding:

1	2	3	4	5	6	7	8	9	10	11	12
blue, orange, green, brown, slate, white, red, black, yellow, violet, rose, aqua	blue, orange, green, brown, slate, white, red, black, yellow, violet, rose, aqua	blue, orange, green, brown, slate, white, red, black, yellow, violet, rose, aqua	blue, orange, green, brown, slate, white, red, black, yellow, violet, rose, aqua	blue, orange, green, brown, slate, white, red, black, yellow, violet, rose, aqua	blue, orange, green, brown, slate, white, red, black, yellow, violet, rose, aqua	blue, orange, green, brown, slate, white, red, black, yellow, violet, rose, aqua	blue, orange, green, brown, slate, white, red, black, yellow, violet, rose, aqua	blue, orange, green, brown, slate, white, red, black, yellow, violet, rose, aqua	blue, orange, green, brown, slate, white, red, black, yellow, violet, rose, aqua	blue, orange, green, brown, slate, white, red, black, yellow, violet, rose, aqua	blue, orange, green, brown, slate, white, red, black, yellow, violet, rose, aqua

Group / Binder

1 / blue
2 / orange
3 / green
4 / brown
5 / slate
6 / white

**DOKUMENTACJA
POWYKONAWCZA**

28.05.2015
Data

KIEROWNIK BUDOWY
Podpis
Krzysztof Zieliński
upr. WKP/00103/OWOE/05

General: Applicable Standards for Cable and Wire

- IEEE Std 1138-2009: IEEE Standard Construction of Composite Fiber Optic Overhead Groundwire (OPGW) for use on Electric Utility Power Lines
- IEC 60794-4-1 Optical Fibre Cables – Part 4-1: Aerial Optical Cables for High-Voltage Power Lines
- European Standard (EN) 50182: Conductors for overhead lines, Round wire concentric lay stranded conductors
- IEC 60104 Aluminium-Magnesium-Silicon Alloy Wire for Overhead Line Conductors
- IEC 61232 Aluminium-Clad Steel Wires for Electrical Purposes
- Fiber Standard: SMF E9 fibers according to ITU-T G.652.D