

DEVICES TECHNICAL DATA / COMPATIBILITY CERTIFICATE

Device No.	K-308	Shell operating press., bar	8	Shell height/length, m	25,176	Tube op. press., bar	-
Equipment type	Tower	Shell test pressure, bar	10	Shell diameter, m	1	Tube test press., bar	-
Department	GP2	Shell operating T, °C	70	Shell material	09G2S/St3sn	Tube operating T, °C	-
Unit		Shell design pressure, bar	5	Shell heat treatment	False	Tube design press, bar	-
Section	S-300	Shell allow pressure, bar	8	Shell cladding material		Tube design T, °C	-
Cost centre No.	1G4106	Shell design T, °C	0	Shell lining		Tube media	-
Exploitation start date	1989	Shell design min T, °C	0	Shell capacity, m³	18,35	Tube sets qty.	-
Manufacturer serial No.	52524	Shell media	10% NaOH, H2S iki 0.45%, oras	Weight empty, kg	10880	Tube lenght, m	-
Identification No.	SI-01-03337	Shell media phase		Weight hydro test, kg	29230	Tubes qty	-
				Tube set weight, kg	-	Tube diameter, mm	-
				Tube set diameter, m	-	Heat ex. area, m²	-
				Tube set capacity, m³	-	Tube material	-

Manufacturer penzchimmaš
Location OL_NPG_GP-2_MGPK_S-300

Notes: Surūdyjės įžeminimas 2007.04.19 2008.08 atlikti nauji skaičiavimai-P-0.8MPa; T-90°C. 2012.05.08 Atlikta vidinių siūlių MT, defektų nenustatyta.2025.05.28 - Atlikti 2026 metais papildomus UTth matavimus VA pratesimui su RBI, taškuose 31; 32; 33; 34; 35; 36; 48; 49.

Flange name	Notification	Flange qty,	Blinded flange qty	Dn	Pn	Flange type	Gaskets				Bolts qty.	Bolts diametr	Bolts length, mm	Bolt length for blinding, mm	Bolt material	Torque [N-m]	Notes
							Type	ID	OD	Width a							
Flanšas	A	12	3	50	40	2*3	Camprofile	61	87		4	M16	100	120	SA 193 GrB7	160 [N-m]	
Flanšas	a_	4		80	16	1*1	Camprofile	95	142		4	M16	100		SA 193 GrB7	160 [N-m]	
Flanšas	B	12		80	40	2*3	Camprofile	90	120		8	M16	100		SA 193 GrB7	160 [N-m]	
Flanšas	b_	2	1	100	16	1*1	Camprofile	118	162		8	M16	100	120	SA 193 GrB7	160 [N-m]	
Flanšas	C	4		100	16	1*1	Camprofile	118	162		8	M16	100		SA 193 GrB7	160 [N-m]	
Flanšas	c_	2		25	40	2*3	Camprofile	35	57		4	M12	90		SA 193 GrB7	60 [N-m]	
Flanšas	D	3	1	50	16	1*1	Camprofile	65	107		4	M16	100	120	SA 193 GrB7	160 [N-m]	
Flanšas	d_	3		50	16	1*1	Camprofile	65	107		4	M16	100		SA 193 GrB7	160 [N-m]	
Flanšas	e_	2		150	16	1*1	Camprofile	170	217		8	M20	120		SA 193 GrB7	300 [N-m]	
Flanšas	f_	4	2	80	16	1*1	Camprofile	95	142		4	M16	100	120	SA 193 GrB7	160 [N-m]	
Liukas	f1_	10		500	16	4*5	Camprofile	539	563		24	M20	140		SA 193 GrB7	350 [N-m]	

DEVICES TECHNICAL DATA / COMPATIBILITY CERTIFICATE

Materials K-308

Flange name	Notification	Category	Nomeclature No.	Description	Quantity
Flanšas	A				
		Tarpinė akliniui	650807000036	Tarpinė laikina Dn50 Pn10-Pn160 MF 61 x 87 s=2 mm TopSil ML-1 DIN2692	6
		Tarpinė	650808000034	Tarpinė Camprofile Dn50 Pn10-Pn100 MF 61 x 87 s=2 mm 1.4541/grafitas DIN2513	12
		Smeigės akliniui	570913030803	Smeigė M16x2.00x120 ASTM A193 Gr.B7, ASME B16.5 / + 2 veržlės ASTM A194 Gr.2H, EN ISO 4032 Heavy Hex (H) m=D, sert.: EN 10204-3.1	12
		Smeigės	570913030627	Smeigė M16x2.00x100 ASTM A193 Gr.B7, ASME B16.5 / + 2 veržlės ASTM A194 Gr.2H, EN ISO 4032 Heavy Hex (H) m=D, sert.: EN 10204-3.1	36
Flanšas	a_				
		Tarpinė	650808000016	Tarpinė Camprofile Dn80 Pn10-Pn40 RF 95 x 121 x 142 s=3 mm 1.4571/grafitas DIN2690	4
		Smeigės	570913030627	Smeigė M16x2.00x100 ASTM A193 Gr.B7, ASME B16.5 / + 2 veržlės ASTM A194 Gr.2H, EN ISO 4032 Heavy Hex (H) m=D, sert.: EN 10204-3.1	16
Flanšas	B				
		Tarpinė	650808000086	Tarpinė Camprofile Dn80 Pn10-Pn100 MF 90 x 120 s=2 mm 1.4571/grafitas DIN2513	12
		Smeigės	570913030627	Smeigė M16x2.00x100 ASTM A193 Gr.B7, ASME B16.5 / + 2 veržlės ASTM A194 Gr.2H, EN ISO 4032 Heavy Hex (H) m=D, sert.: EN 10204-3.1	96
Flanšas	b_				
		Tarpinė akliniui	650807000003	Tarpinė laikina Dn100 Pn10-Pn16 RF 115 x 162 s=2 mm TopSil ML-1 DIN2690	2
		Tarpinė	650808000087	Tarpinė Camprofile Dn100 Pn10-Pn16 RF 118 x 144 x 162 s=3 mm 1.4571/grafitas DIN2690	2
		Smeigės akliniui	570913030803	Smeigė M16x2.00x120 ASTM A193 Gr.B7, ASME B16.5 / + 2 veržlės ASTM A194 Gr.2H, EN ISO 4032 Heavy Hex (H) m=D, sert.: EN 10204-3.1	8
		Smeigės	570913030627	Smeigė M16x2.00x100 ASTM A193 Gr.B7, ASME B16.5 / + 2 veržlės ASTM A194 Gr.2H, EN ISO 4032 Heavy Hex (H) m=D, sert.: EN 10204-3.1	8
Flanšas	C				
		Tarpinė	650808000087	Tarpinė Camprofile Dn100 Pn10-Pn16 RF 118 x 144 x 162 s=3 mm 1.4571/grafitas DIN2690	4
		Smeigės	570913030627	Smeigė M16x2.00x100 ASTM A193 Gr.B7, ASME B16.5 / + 2 veržlės ASTM A194 Gr.2H, EN ISO 4032 Heavy Hex (H) m=D, sert.: EN 10204-3.1	32
Flanšas	c_				
		Tarpinė	650808000044	Tarpinė Camprofile Dn25 Pn10-Pn100 MF 35 x 57 s=2 mm 1.4571/grafitas DIN2513	2
		Smeigės	570913030702	Smeigė M12x1.75x90 ASTM A193 Gr.B7, ASME B16.5 / + 2 veržlės ASTM A194 Gr.2H, EN ISO 4032 Heavy Hex (H) m=D, sert.: EN 10204-3.1	8
Flanšas	D				
		Tarpinė akliniui	650807000034	Tarpinė laikina Dn50 Pn10-Pn40 RF 61 x 107 s=2 mm TopSil ML-1	2
RegimantasSv					09-15-2025
					Page 2 of 3

DEVICES TECHNICAL DATA / COMPATIBILITY CERTIFICATE

Materials K-308					
Flange name	Notification	Category	Nomeclature No.	Description	Quantity
		Tarpinė	650808000493	Tarpinė Camprofile Dn50 Pn10-Pn40 RF 65 x 87 x 107 s=3 mm 1.4541/grafitas DIN2690	3
		Smeigės aklinimui	570913030803	Smeigė M16x2.00x120 ASTM A193 Gr.B7, ASME B16.5 / + 2 veržlės ASTM A194 Gr.2H, EN ISO 4032 Heavy Hex (H) m=D, sert.: EN 10204-3.1	4
		Smeigės	570913030627	Smeigė M16x2.00x100 ASTM A193 Gr.B7, ASME B16.5 / + 2 veržlės ASTM A194 Gr.2H, EN ISO 4032 Heavy Hex (H) m=D, sert.: EN 10204-3.1	8
Flanšas	d_				
		Tarpinė	650808000493	Tarpinė Camprofile Dn50 Pn10-Pn40 RF 65 x 87 x 107 s=3 mm 1.4541/grafitas DIN2690	3
		Smeigės	570913030627	Smeigė M16x2.00x100 ASTM A193 Gr.B7, ASME B16.5 / + 2 veržlės ASTM A194 Gr.2H, EN ISO 4032 Heavy Hex (H) m=D, sert.: EN 10204-3.1	12
Flanšas	e_				
		Tarpinė	650808000005	Tarpinė Camprofile Dn150 Pn10-Pn16 RF 170 x 204 x 217 s=3 mm 1.4541/grafitas DIN2690	2
		Smeigės	570913030628	Smeigė M20x2.50x120 ASTM A193 Gr.B7, ASME B16.5 / + 2 veržlės ASTM A194 Gr.2H, EN ISO 4032 Heavy Hex (H) m=D, sert.: EN 10204-3.1	16
Flanšas	f_				
		Tarpinė aklinimui	650807000024	Tarpinė laikina Dn80 Pn10-Pn40 RF 90 x 142 s=2 mm TopSil ML-1 DIN2690	4
		Tarpinė	650808000016	Tarpinė Camprofile Dn80 Pn10-Pn40 RF 95 x 121 x 142 s=3 mm 1.4571/grafitas DIN2690	4
		Smeigės aklinimui	570913030803	Smeigė M16x2.00x120 ASTM A193 Gr.B7, ASME B16.5 / + 2 veržlės ASTM A194 Gr.2H, EN ISO 4032 Heavy Hex (H) m=D, sert.: EN 10204-3.1	8
		Smeigės	570913030627	Smeigė M16x2.00x100 ASTM A193 Gr.B7, ASME B16.5 / + 2 veržlės ASTM A194 Gr.2H, EN ISO 4032 Heavy Hex (H) m=D, sert.: EN 10204-3.1	8
Liukas	f1_				
		Tarpinė	650808000102	Tarpinė aparatų Camprofile Dn500 Pn10-Pn160 539 x 563 s=3 mm 1.4571/grafitas	10
		Smeigės	570913030690	Smeigė M20x2.50x140 ASTM A193 Gr.B7, ASME B16.5 / + 2 veržlės ASTM A194 Gr.2H, EN ISO 4032 Heavy Hex (H) m=D, sert.: EN 10204-3.1	240