

Pavadinimas	Vienetai	Kiekis
CU1SB024T06RNN1BR CU1S Ex combination unit 24VDC, Ex de IIB,2G 10J 60fpm,116db 1m 27xTone, 1xM20, Red / SL250801 QNHS-WS-24-R-ATEX-M20 Ex combined electronic sounder 118dB(A) & TOP LED signal beacon with convenient selection of steady, flashing, strobe, and simulated revolving operation (Red), Ex 2G Ex db IIC T6 Gb, IP66, -40°C +55°C, Materials: Housing-Al, Horn housing-PC, Lens-Tempered glass, Filter-PC (Red), 12-24V DC, max 1,4 A, pedestal mount, 1xM20, ATEX & IECEx	vnt.	8
~~SL250801~~ ~~QNHS-WS-24-R-ATEX-M20~~ ~~Ex combined electronic sounder 118dB(A) & TOP LED signal beacon with convenient selection of steady,~~ ~~flashing, strobe, and simulated revolving operation (Red),~~ ~~Ex 2G Ex db IIC T6 Gb, IP66, -40°C +55°C,~~ ~~Materials: Housing-Al, Horn housing-PC,~~ ~~Lens-Tempered glass, Filter-PC (Red),~~ ~~12-24V DC, max 1,4 A, pedestal mount, 1xM20, ATEX & IECEx~~ ~~Lens-Tempered glass, Filter-PC (Red),~~ ~~12-24V DC, max 1,4 A, pedestal mount, 1xM20, ATEX & IECEx~~	~~vnt.~~	~~1~~
SL6474121-1 CZ6474/121B-LEDRGY05W-07-4-F1B-DA3 5W/50lm/ 2W buzeris , 80dB @30cm	vnt.	13